

Coolants

www.HarryMillerCorp.com

Contact Us: +1.215.324.4000

Synthetics

Hamikleer® 1975 Series

A range of synthetic coolants that offer varying levels of lubrication. Low foaming with excellent tramp oil rejection. The GP version offers galvanic protection with aluminum, brass and steel combinations.

Hamikleer® 1980-MR/MRX

Synthetic machining lubricant/coolant for ferrous and non-ferrous metals. Bio-stable and low foaming. Offers more lubrication for medium-duty machining operations.

Hamikleer® 1883-2TM

Excellent corrosion protection, especially formulated for tube mill rolling.

Hamikleer® X-231-HWL

Synthetic grinding and machining fluid for lighter-duty operations. Provides excellent rust protection. Will not stain brass, copper or aluminum alloys or turn rancid. OSHA acceptable lubricant with no petroleum oils, phenols, sulphur, halogens, nitrates or heavy metals.

Semi-Synthetics

Kleerkut® 2900

Versatile coolant with extreme pressure additives that can work on all metals. Provides enhanced corrosion protection.

Kleerkut® 2900-AL

Versatile, non-chlorinated with extreme pressure additives for use on all metals. Keeps machines clean. Free of substances that require reporting under SARA Title III.

Kleerkut® 4900 Series

The latest in semi-synthetic technology. These micro-emulsions are low foaming with excellent bio-stability. Series versions offer varying levels of lubrication for machining and grinding on a wide range of materials, including high-strength alloys.

Kleerkut® 4960-LT

A low-foaming, bio-resistant coolant capable of performing a wide variety of machining/grinding/stamping operations on both ferrous and non-ferrous metals. An enhanced lubrication package makes it particularly effective on aluminum & oxygen-free copper.

Kleerkut® 4960-RP2

A premium low-foaming coolant specially formulated for aluminum.

Kleerkut® 5900

Chlorinated, micro-emulsion product with superior emulsion stability for ferrous and yellow materials. Very low foaming.

Water-Soluble Oils

Hamikut® 100

Our newest technology, this is a non-chlorinated soluble oil offering excellent bio-resistance. Low foaming, this product offers superior rust protection. Ideal for use in central systems.

Hamikut® 100-MG3

Non-chlorinated soluble oil designed for use on magnesium. This oil offers superior emulsion stability with high tolerance to hard water contamination.

Hamikut® 9036 Series

Product line for heavy-duty machining of ferrous and non-ferrous materials. Excellent emulsion stability and low foaming, with versions designed for high-pressure machines and for use with soft water.

Manufactured By:



4309 N. Lawrence Street
Philadelphia, PA 19140
USA

Harry Miller Corp offers a superior line of coolants for metalworking, including custom formulations. Our solutions are matched to your process, your products and your way of doing business.

Harry Miller Corp also offers a full line of aqueous and petroleum-based rust inhibitors, drawing and stamping fluids, cleaners, acid pickling solutions and non-destructive testing fluids.



Your Sales Rep/Distributor: